

sublioncotton

STEP 2

PRINTER INSTALATION

Install the printer using original Epson DVD (included) fill the ink tanks using only original sublimation color's (included in the package).





Setup the PRINTER PREFERENCES - PROPERTIES Go to CONTROL PANEL - PRINTER AND FAXES Choose your printer (right click) then choose PRINTING PREFERENCES - PROPERTIES

Postavke i	spisa za EPSON	L300 Series		×
Main More Options Maintenance				
Printing Presets				
Add/Remove Presets	Document Size	A4 210 x 297 r	nm	~
 Document - Fast Document - Standard Quality Document - High Quality 	Orientation	Portrait		
Document - 2-Up	Paper Type	plain papers		~
Document - Grayscale	Quality	Standard		~
SUBLIMATION PROFILE	Color	Color	⊖ Grayscale	
	2-Sided Printin	g	Settings	
	Multi-Page	Off	♥ Page Order	
	Copies 1	•		
	Print Previe		Quiet Mode	-
Reset Defaults Ink Levels			Show Settings	
	U redu	Odustani	Primijeni Pomoć	

1.1 Set up Paper Type: plain papers Quality: Standard

Important: Do NOT select some other settings, the print will NOT be good.

Tip: The paper does not apsorb ink. So high print quality and paper type change will only make bad result when applying to textiles.

STEP 4

Click More Options tab.

On color corection click Custom and then choose Advanced.

Postavke is	spisa za EPSON	L300 Series		×
Main More Options Maintenance				_
Printing Presets	Document Size	A4 210 x 297 mm	*	
Add/Remove Presets	Output Paper	Same as Document Siz	e v	
 Document - Fast Document - Standard Quality Document - High Quality 	Reduce/Enlarge Fit to Page	e Document Zoom to	* %	
Document - 2-Up Document - Fast Grayscale Document - Grayscale SUBLIMATION PROFILE	Color Correction	Custom	Advanced	
	Watermark	None Add/Delete	✓ Settings	
	Header/Footer		Settings	
	Additional Settings Rotate 180° High Speed			
Reset Defaults			Show Settings	
	U redu	Odustani Prim	nijeni Pomoć	

Setup Options as on image below.

			Color C	orrection			
Color Management	_						
Color Controls							_
PhotoEnhance				a second a second	malarrant	Statistics.	and an and
					within the state of the state	1000 (100)	And a second second
O No Color Adjustm	ent		_		addas socializadores lastalas socializadores contra de las destructuras contra de las destructuras localidas destructuras en		
				- Alterna	make supplications		
Color Mode	Adobe R	GB	~	No. All of property but to and production cost - contributions of a set -	20.00	No. 51 of Control And Social Control of Control of Control Control of Control of Control of Control Control of Control of	20.00
Gamma	1.8		~	Read Bridge Bridge	A CONTRACTOR	And A Residences of the second	
Color Adjustment	Method			<original< td=""><td>Photo></td><td><previe< td=""><td>w></td></previe<></td></original<>	Photo>	<previe< td=""><td>w></td></previe<>	w>
O Color Circle) Slide Bar					
0.000	`						
		Reset Co	ntrols				
Brightness 10		. 0	· +	🌢 Cyan	5	, O	
					-		+
Contrast 0	1	- Q		🍐 Magenta	-10	-Q	
Ū	-		'+	•			+
	1	0					
Saturation 0	- '	Ť	'+	Yellow	-10 -	· ·	+
					ОК	Cancel	Help

1.2 Set up color setings

Important: This is a printing technique used to apply vector ans less demanding graphics on textile. This technique is not made for printing high quality photos.

STEP 6

Use the Mirror Image Option.

Postavke	ispisa za EPSON	L300 Series	
Main More Options Maintenance			
Printing Presets	Document Size	A4 210 x 297 mm	~
Add/Remove Presets	Output Paper	Same as Document S	iize 🗸 🗸
Document - Fast	Reduce/Enlarg	e Document	
Document - Standard Quality Document - High Quality	Fit to Page	O Zoom to	* %
Document - 2-Up	Color Correction		
Document - Grayscale	 Automatic 	Custom	Advanced
SUBLIMATION PROFILE			Image Options
	Watermark	None	~
		Add/Delete	Settings
	Header/Footer		Settings
	Additional Settings	S	
	Rotate 180°	,	
	✓ High Speed		
	✓ Mirror Image	2	
Reset Defaults	-		Show Settings
			g
	U redu	Odustani Pri	mijeni Pomoć

Adjust printing options in Corel Draw in next few steps.

1. Select the printer: Epson L300

2. Click the Color tab

Dest	ination			
Pri <u>n</u>	iter:	EPSON L300 Series	~	Preferences
P <u>ag</u>	e:	Match orientation (Portrait)	¥	Us <u>e</u> PPD
Stat		Ready		
	ation: nment:	USB004		Print to file
Print	range		Copies	
00	Cu <u>r</u> rent do	ocument ODocuments	Number of copies:	1
\odot	C <u>u</u> rrent pa	ge <u>S</u> election		
OF	ages:	7	كر كر كر	Collate
		Even & Odd 🗸 🤟	Print as <u>b</u> itmap:	300 🔺 dpi
Print s	t <u>y</u> le:	Custom (Current settings not saved)		✓ Sa <u>v</u> e As



STEP 8

Use the exect profile as on the picture below.

			Print composite		
			O Print separations		
			Use document color settings		
			○ Use color proof settings		
Color conversion	ons performe	d by:	CorelDRAW	~	
Output colors as:		RGB	¥		
			Convert spot colors to RGB		
Correct colors	using color p	ofile:	sRGB IEC61966-2-1 black scaled 🗸 🗸		
			✓ Preserve RGB numbers		
			Preserve pure black	srgb_iec61966-2-1 c:\program files\cor	el\coreld
Rendering intent:		Relative colorimetric	x7\color\srgb_iec61966-2-1 2.98 KB		
	ettings and p you selected		this dialog box are set for the Windo o.	ows Graphic device	

🖶 Postavke i	spisa za EPSON	L300 Series		×
Main More Options Maintenance				
Printing Presets				
Add/Remove Presets	Document Size	A4 210 x 297 m	m	~
Document - Fast				
Document - Standard Quality Document - High Quality	Orientation	Portrait	OLandscape	
12 Document - 2-Up	Paper Type	plain papers		۷
Document - Grayscale	Quality	Standard		~
SUBLIMATION PROFILE	Color	Color	◯ Grayscale	_
	2-Sided Printin	9	Settings	
			_	_
	Multi-Page	Off 🗸	Page Order	
	Copies 1	÷	11 22 33	
		Collate	Reverse Order	
	Print Previe	ew	Quiet Mode	- 1
	Job Arrang	er Lite		_
Reset Defaults Ink Levels			Show Settings	:
	U redu	Odustani	Primijeni	oć

1.9 Save your settings: After you made all settings go on tab Add/Remove Presets name your setings (SubliOnCotton)

ustom Settings				
inting Presets			Name	
💕 ivanina kuća bajiki		^	sublioncotton	
💕 crveni križ			Icon	
💕 zmaj anđelko				
💕 kornjačica rita			<i>~~~</i>	N DD D
💕 neustrašiva mama			<	>
💕 šalice kim			Comments (optional)	
🚺 Deez crno bjeli				
💕 deez lonček krokodil				~
💕 volim ljuto iz pdf-a 11/	2018			
💕 Sublimacija na pamuk				\sim
💕 sublimacija na pamuk A	13		Date and Time	
👏 sublioncotton		<u> </u>	2/15/2019 7:56:23 AM	
		*	2/13/2013 7.30.23 AM	
Show Hide	Delete	Reset		Save
Items	Current	: Settings	Registered Settings	^
Paper Source	Rear Pa	per Feed	Rear Paper Feed	
Document Size	A4 210	x 297 mm	A3 297 x 420 mm	100
Orientation	Portrait		Portrait	
Paper Type	plain pa	pers	plain papers	
	Standar	d	Standard	
Quality				
Quality Quality Detail	-		-	~

STEP 10

1.8 How to apply: After you print your design, pull the paper through coating powder. Pre-heat your garment for 5-10 sec. Put your design on the garment Important: be careful NOT to move a print. Wet ink and coating powder on your design are sensitive before fixing. When you put your design on T-shirt heat apply for 35 sec. on 185° PEEL on full COOLD.



T-shirt Print Box supported by

You can also use your printer!

You can use only ink jet printers with micro piezo print heads. The models that is recommended to use is Epson L serie, (L310 and L1300), (Epson ITS serie I3060 I3070),(Ricoh SG 3110 DN)

Adaped printers

We are using adapted printer for this technique. As the ink on the paper is wet when the print outputs from the printer the transport wheels are scratching our design so we have to remove them.

How to remove the transport wheels?

In next page we will show you how to remove transport wheels in few minutes.

How to remove the transport wheels?

Remove two screws () Remove wheel carrier (Remove 9 wheels () Leave 2 wheels () Return wheel cerrier () Return two screws ()



